

Make the shift to next generation OCZ Vertex 460 SSD. Combining OCZ's own controller design with the latest generation of flash, Vertex 460 keeps your computing experience ahead of the game. A faster, snappier, and more reliable system is what you can expect from a high-performance yet value-minded Vertex 460 upgrade.

It's storage for your multimedia, multitasking world

The OCZ Vertex 460 Series delivers the performance, productivity, and energy efficiency your system is craving. Say goodbye to lag and get a computing experience worthy of your time.



Performance that matters

Do you write a lot of data? Vertex 460 delivers leading write speeds that you won't get with any other solution. No fancy behind-the-scenes tricks, just pure storage performance.

Reliability and durability from the inside out

With quality SSD technology built into every drive, the Vertex 460 Series is built to provide years of hard drive-humiliating performance. Ditch that spinning HDD for some storage peace of mind.

Product Highlights

- Proprietary Barefoot 3 M10 controller technology delivers superior performance and endurance, combined with the latest generation 19nm flash as OCZ's most cost-effective SSD upgrade option
- Advanced suite of NAND flash management keeps your drive at higher sustained performance over the long term
- Designed for ultimate reliability at an excellent value with in-house technology and high quality components
- Putting emphasis on client workload endurance, rated at 20GB/day of host writes for 3 years
- Excels in both incompressible and compressible data types such as multimedia, encrypted data,. ZIP files and software
- Bundled with a 3.5-inch desktop adapter bracket and Acronis® True Image™ cloning software to easily transfer data from your old hard drive
- Sleek alloy housing offers slimmer 7mm z-height for compatibility with the ultra-thin notebooks

Performance Refined

Start fast and stay fast with consistently high speeds and mixed workload performance in client workstation applications.

	120GB	240GB	480GB
Max Read ¹	530 MB/s	540 MB/s	545 MB/s
Max Write ¹	420 MB/s	525 MB/s	525 MB/s
Random Read (4K QD32) ²	80,000 IOPS	85,000 IOPS	95,000 IOPS
Random Write (4K QD32) ²	90,000 IOPS	90,000 IOPS	90,000 IOPS
Steady State Random Write (4K QD32)3	12,000 IOPS	21,000 IOPS	23,000 IOPS

- Maximum sequential speeds measured with ATTO
- 2. Measured with Crystal Disk Mark, 1000MB file size, QD32
- 3. Measured with lometer 2010, 12 hour precondition to SNIA guidelines



PHYSICAL SPECIFICATIONS

Usable Capacities 120GB, 240GB, 480GB

19nm Multi-Level Cell (MLC) Flash NAND Components

SATA 3.0 6Gb/s Interface

Barefoot 3 M10 Controller

Form Factor 2.5-inch; ultra-slim 7mm

99.7 (L) x 69.75 (W) x 7mm (H) Dimensions

Drive Weight 113g

MODEL	PART NUMBER	UPC
120GB	VTX460-25SAT3-120G	842024036234
240GB	VTX460-25SAT3-240G	842024036241
480GB	VTX460-25SAT3-480G	842024036258

RELIABILITY / SECURITY SPECIFICATIONS

Data Path Protection BCH ECC corrects up to 44 random bits/1KB

Self-Monitoring, Analysis and Reporting Technology (SMART) Support Product Health Monitoring

Endurance Rated for 20GB/day of host writes for 3 years under typical client workloads

AES-256 Encryption

MTBF 2 million hours

COMPATIBILITY

Standard SATA power connector; Fully compliant with Serial ATA International Serial ATA

Organization: Serial ATA Revision 3.0. Fully compliant with ATA/ATAPI-8 Standard

Native Command Queuing (NCQ)

Operating Systems Windows, Mac, Linux

Targeted Applications Client workstations and laptops

ENVIRONMENTAL SPECIFICATIONS

Idle: 0.60W Active: 2.70W Power Consumption

0°C ~ 70°C Operating Temperature

-45°C ~ 85°C Storage Temperature

Shock Resistance 1500G/0.5ms

Vibration (Operational) 2.17Grms (7-800Hz)

Vibration (Non-Operational) 16.3Grms (20-2000Hz)

UL C/US, FCC, CE, C-Tick, KCC, BSMI, VCCI, WEEE Certifications

ADDITIONAL

Performance Optimizations TRIM (requires OS support), Idle Time Garbage Collection

Acronis True Image HD cloning software (Windows 8 and below) registration key; 3.5" Package Contents

desktop adaptor

3-Year Warranty, Toll-Free Tech Support, 24 Hour Forum Support Warranty